

Attorney Docket No.: SAM-0069
Application Serial No.: 09/273,643
Reply to Office Action of: October 22, 2003

Amendments to the Claims:

Please amend claims 1, 2, 5, 13, 14, and 17 as follows.

This listing of claims replaces all prior versions, and listings, of claims in the application.

Listing of claims:

- B¹
1. (currently amended) An imaging apparatus comprising:
first signal processing means for partitioning the level of an analog image signal into a plurality of sections, and for amplifying the analog image signal by a plurality of gains according to each of the plurality of sections section, at least two of the sections having different corresponding gains; and
second signal processing means for converting the analog image signal amplified by the different gains into a first digital signal, and for non-linearly gamma-correcting the first digital signal according to the plurality of sections on which the amplification of the analog image signal by the first signal processing means is based each section.
 2. (currently amended) The imaging apparatus of claim 1, wherein the first signal processing means comprises:
an analog-to-digital converter for converting the analog image signal into a first digital signal for partitioning the analog image signal level into the plurality of sections;
a gain selector for selecting the corresponding gain from the plurality of different gains according to each of the plurality of sections section, and for outputting the selected gain; and
an amplifier for amplifying the analog image signal by the gain output from the gain selector.
 3. (original) The imaging apparatus of claim 2, wherein the plurality of different gains are provided by a microcomputer.

Attorney Docket No.: SAM-0069
Application Serial No.: 09/273,643
Reply to Office Action of: October 22, 2003

4. (original) The imaging apparatus of claim 2, wherein the plurality of different gains are approximately inversely proportional to the luminance level of the analog image signal.
5. (currently amended) The imaging apparatus of claim 1, wherein the second signal processing means comprises:
- an analog-to-digital converter for converting the image signal amplified by the plurality of different gains into a second digital signal; and
 - a gamma corrector for non-linearly gamma-correcting the second digital signal according to the plurality of sections on which the amplification of the analog image signal by the first signal processing means is based each section.
6. (original) The imaging apparatus of claim 1, further comprising a chrominance controller for controlling chrominance gain of the non-linearly gamma corrected digital output of the second signal processing means.
7. (original) The imaging apparatus of claim 6, wherein the chrominance controller comprises:
- a low pass filter for passing a low-frequency component of the non-linearly gamma corrected digital output of the second means, to output a luminance signal;
 - a chrominance gain selector for partitioning the level of the luminance signal into a plurality of second sections, and for selectively outputting a corresponding second gain among a plurality of different second gains according to each section;
 - a high pass filter for passing a high frequency component of the non-linearly gamma corrected digital output of the second means, to output a chrominance signal;
 - a multiplier for multiplying the chrominance signal by the corresponding second gain from the chrominance gain selector;
 - an adder for adding the output of the multiplier to the luminance signal;
 - a divider for dividing the output of the adder by approximately 2; and

Attorney Docket No.: SAM-0069
Application Serial No.: 09/273,643
Reply to Office Action of: October 22, 2003

a clipper for outputting a digital 0 if the output of the divider is less than 0, and for outputting the maximum value of the output of the second signal processing means if the output of the divider is greater than the maximum value of the output of the second signal processing means.

8. (original) The imaging apparatus of claim 7, wherein the plurality of different second gains are approximately inversely proportional to the level of the luminance signal.

9. (original) An imaging apparatus comprising:
an amplifier for amplifying an analog image signal by a predetermined gain;
an analog-to-digital converter for converting the amplified analog image signal into a digital signal;
a chrominance controller for controlling chrominance gain of the converted output of the analog-to-digital converter; and
a digital signal processor for processing the output of the chrominance controller.

10. (original) The imaging apparatus of claim 9, wherein the chrominance controller comprises:

a low pass filter for passing a low-frequency component of the converted output of the analog-to-digital converter, to output a luminance signal;

a chrominance gain selector for dividing the level of the luminance signal into a plurality of sections, and for selectively outputting a corresponding gain among the plurality of different gains according to each section;

a high pass filter for passing a high frequency component of the converted output of the analog-to-digital converter, to output a chrominance signal;

a multiplier for multiplying the chrominance signal by the corresponding gain output from the chrominance gain selector;

an adder for adding the output of the multiplier to the luminance signal;

Attorney Docket No.: SAM-0069
Application Serial No.: 09/273,643
Reply to Office Action of: October 22, 2003

a divider for dividing the output of the adder by a factor; and
a clipper for outputting a digital 0 if the output of the divider is less than 0, and for outputting the maximum value of the output of the analog-to-digital converter if the output of the divider is greater than the maximum value of the output of the analog-to-digital converter.

11. (original) The imaging apparatus of claim 10, wherein the plurality of different gains are approximately inversely proportional to the level of the luminance signal.
12. (original) The imaging apparatus of claim 10, wherein the factor is approximately 2.
13. (currently amended) An image signal processing method comprising:
partitioning the level of an analog image signal into a plurality of sections, and amplifying the image signal by a plurality of different gains according to each of the plurality of sections section, at least two of the sections having different corresponding gains; and
converting the image signal amplified by the plurality of different gains into a first digital signal, and non-linearly gamma-correcting the first digital signal according to the plurality of sections on which the amplification of the analog image signal by the first signal processing means is based each section.
14. (currently amended) The method of claim 13, wherein partitioning comprises:
converting the analog image signal into a first digital signal for partitioning the analog image signal level into the plurality of sections;
selecting the corresponding gain among the plurality of different gains according to each of the plurality of sections section; and
amplifying the analog image signal by the selected gain.

Attorney Docket No.: SAM-0069
Application Serial No.: 09/273,643
Reply to Office Action of: October 22, 2003

15. (original) The method of claim 14, wherein the plurality of different gains are provided by a microcomputer.
16. (original) The method of claim 14, wherein the plurality of different gains are approximately inversely proportional to the luminance level of the analog image signal.
17. (currently amended) The method of claim 13, wherein converting comprises:
converting the image signal amplified by the plurality of different gains into a second digital signal; and
non-linearly gamma-correcting the second digital signal according to the plurality of sections on which the amplification of the analog image signal by the first signal processing means is based each section.
18. (original) The method of claim 13, further comprising controlling chrominance gain of the non-linearly gamma-corrected second digital signal.
19. (previously presented) The method of claim 18, wherein controlling comprises:
passing a low-frequency component of the non-linearly gamma-corrected digital signal, to output a luminance signal;
partitioning the level of the luminance signal into a plurality of second sections, and selecting a corresponding second gain among a plurality of different second gains according to each second section;
passing a high-frequency component of the non-linearly gamma-corrected digital signal, to output a chrominance signal;
multiplying the chrominance signal by the corresponding selected second gain;
adding the result of the multiply to the luminance signal;
dividing the result of the add by approximately 2; and
clipping to 0 if the result of the division is less than 0, and clipping to the maximum value of the gamma-corrected digital signal if the result of the division is

Attorney Docket No.: SAM-0069
Application Serial No.: 09/273,643
Reply to Office Action of: October 22, 2003

*B1
cont.*

greater than the maximum value of the gamma-corrected digital signal, and outputting the result.

20. (original) The method of claim 19, wherein the plurality of second gains are approximately proportional to the luminance level of the analog image signal.
